

# AC 550

Cummins  
Mecc Alte  
D+ &



ISO8528

GC ; ) &

SZUTEST

GC - \$\$\$



2000/14/EC

&\$\$\$#( #

z) \$ z' \$z 'D:

	"	"	"	"	Amp
400/230	550,00	440,00	500,00	400,00	721,00

fP GDE

GC ; ) &

) & z

fDF DE

%&

GC " \$(\*\*

z&(

GC

## Standard Specifications

z

fl

E

z

z

## ALTERNATOR

## TRANSFER SWITCH

# AC 550

Cummins  
Mecc Alte  
D+' &'

Manufacturer		Cummins		
Model		QSX 15 G8		
		% \$\$\$' "# "		
		) \$\$\$\$' "		
		0 + \$\$\$ < DQ		
	L	15,000		
	"	137 x 169		
		17,0:1		
	fl # 7	"# "	1500	
	fl 7	L	91,00	
		L	66,00	
AbsorbedAirDischargeReSourceKey.Text	' # "	36,30		
	' # "	637,00		
fl ' # 7	' # "	82,20		
	° C	515,00		
		24 V d.c.		
	Load	% \$ \$ i	' + ) i	) \$ i
	# "	105,00	79,00	55,00

		Mecc Alte		
		ECO 40-3S		
	Hz	50		
	"	500,00		
7 cg'		0,80		
		3		
	fl 7	400/230		
	A	721,00		
Temperature		H		

		fl 7		fl 7	
	"	"	"	"	L
AC 550	3850,00	3407,00	1550,00	2103,00	850,00
		fl 7		fl 7	
	"	"	"	"	L
MS 80	4850	4750	1560	2490	850



# AC 550

Cummins  
Mecc Alte  
D+ &

f@z@Bl  
f@z@Bl

"z" "z"

f@z@Bl

971

#

#

#

#

#

6G'9B'\*\$-\$)'\$

6G'9B'\*\$\$\$!\*!&

6G'9B'\*\$\$\$!\*!(

f&%) +L

f&)(, L

f&% \$L

GA 8

!&+""

%, !&\*(

&(\$)

ž

ž

ž

ž

# AC 550

Cummins  
Mecc Alte  
D+ & T



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 in front and back side special large access doors for easy maintenance
- 9 Base frame -fuel tank.
- 10 Lifting points similar to ISO container , located on each top corner of the canopy
- 11 the canopy provides easy access to radiator cap.
- 12 sound proofing materials
- 13 Plastic air intake pockets.

	"	1560
fl "L	"	4750
fl "L	"	2490
	L	850